


CRYSTAL CONTROLLED MASTER CLOCK / TIME CODE GENERATOR

The **ES-160A** is a Master Clock/Time Code Generator. The unit employs a voltage controlled/temperature compensated crystal oscillator which provides the **ES-160A** with an accuracy of one second per month. Six .56" yellow LED's display real time while the unit simultaneously generates several types of time (and date) code (SMPTE/EBU, **ESE-TC89**, **ESE-TC90** and RS232C/ASCII) and a 1 PPS signal.

Since the **ES-160A** is a completely self-contained unit with no link to GPS, USNO or WWV, it is a practical alternative where users have a concern over the "availability" of such time references. The **ES-160A** is designed as a "primary" Master Clock. However, the unit is an excellent choice for use as a "secondary" Master Clock in a system utilizing an Automatic Master Clock Switcher (**ES-150**) and any other Master Clock with an **ESE** Time Code output.

Features:

- SMPTE/EBU, ASCII (RS-232C) and **ESE** (TC89 & TC90) Time Code Outputs
- 12 or 24 Hour Display
- Automatic Daylight Savings Time Correction
- One Second per Month "VCTCXO" Crystal Accuracy
- Rugged Rack Mount Enclosure
- 10-Hour Battery Back-Up
- 6-Digit .56" LED Display
- External Time Sync Input
- Simple Operation & Installation
- Several Options Available as well as Custom Modifications
- 1 PPS Output



Real Time (Hour, Minute & Second) and Gregorian Date (Month, Day & Year) are set via the front panel mounted "Set" switch. A rear mounted "Enable" switch is provided to protect the unit from accidental setting. Once set, the unit can be synchronized "manually" to any source of reliable time via the "Set" switch or "automatically" via the External Sync Input.

Software is also supplied with the **ES-160A** permitting the user to continuously update a computer's DOS or Windows® clock to the UTC (Coordinated Universal Time) available on the ASCII output.

Specifications

Electrical: 117 VAC, 50/60 Hz
Power: 15 Watts Maximum
Mechanical: 1.75" x 19" Rack Mount, 10" Deep
Displays: Six Digits, Yellow LED, .56" High
Accuracy: +/-33mS/day
Video Input: RS-170A Composite Video/Blackburst, 1 Vpp, 75Ω
Time Sync Input: TTL, 1 PPS or Slower

Outputs: 1 PPS: TTL, 50% Duty Cycle
ESE Time Code: drives 100 Slaves @ 4000'
SMPTE: 600Ω Balanced or Unbalanced
RS-232C: ASCII Date & Time @ 9600 Baud,
8 Data, No Parity, 1 Stop
Battery: 10-Hour Back-Up of CPU
(displays are blank)
Options: B, Black, EBU, EXT, HR, J, UL

